

Raport danych numerycznych



Data pomiaru: 26.08.2024 14:25:54
Bocznica:
Tor: 102

Tolerancje parametrów:

20km/h

-10 < Szerokość < 32

-25 < Przechyłka < 25

-50 < Nierówność pionowa < 50

-53 < Nierówność pozioma < 53

-30 < Wichrowatość toru < 30

-4 < Gradient toru < 4

W - Podkład			R - Rozjazd				Zdarzenia
Przebieg [km]	Szer. [mm]	Przech. [mm]	Nier. pion. (10[m]) [mm]	Nier. poz. (10[m]) [mm]	Wich. toru (5[m]) [mm]	Grad. (1[m]) [mm]	
#0.5800	4.1	3.1			---	8.1 #	R
0.5750	-1.0	8.5	12.1	32.1	-2.2	0.4	R
0.5700	2.4	-7.0	-1.2	23.9	-6.4	-2.3	R
0.5650	-2.2	1.0	-19.5	24.8	11.3	1.2	R
0.5600	0.0	13.2	6.4	33.5	10.8	2.7	R
0.5550	-0.2	22.3	1.9	33.4	8.1	-1.2	R
0.5500	3.2	28.6	14.2	41.7	-0.7	-2.2	
#0.5450	13.1	22.4	-10.7	58.2	-10.1	-4.7 #	R
0.5400	5.1	13.1	3.8	44.7	-1.5	0.1	R
0.5350	-2.5	9.6	2.1	20.6	-11.7	-1.0	R
0.5300	4.5	-1.1	-11.8	38.4	-1.7	-2.6	R
0.5250	0.8	0.6	-6.3	51.4	1.4	0.0	R
0.5200	0.5	-2.7	19.0	39.2	-6.9	4.0	R
0.5150	2.6	-4.8	-22.4	36.8	5.0	-3.0	
0.5100	0.8	10.7	27.3	33.2	11.9	2.7	
0.5050	-2.7	9.6	-1.8	23.1	-4.7	1.5	
0.5000	-3.9	9.6	-11.0	33.5	2.0	1.1	
#0.4950	-4.4	9.9	-3.4	22.9	2.3	-1.1	W
0.4900	-2.0	4.4	-1.0	30.9	-13.0	1.6	
0.4850	-2.3	-2.8	-3.4	30.7	-2.2	0.2	
0.4800	-1.3	-4.3	15.3	27.0	-1.6	-1.5	
0.4750	-3.3	2.5	-5.6	22.9	17.2	2.5	
0.4700	-1.4	17.3	12.3	21.6	0.3	-0.7	
0.4650	-2.9	5.5	-16.8	23.3	-14.2	-0.2	
0.4600	-3.5	-8.7	-3.7	21.6	-11.3	-1.0	
0.4550	-4.0	-6.2	8.5	32.7	12.7	1.7	
0.4500	-1.9	-9.6	-2.7	27.8	-16.2	0.7	
0.4450	-4.8	-3.5	5.8	21.9	18.4	1.2	W
0.4400	-4.9	5.0	1.4	34.5	3.1	1.8	
0.4350	-2.6	2.2	0.3	19.0	-5.0	-0.4	
0.4300	-3.5	-5.3	-18.6	17.6	-7.9	1.7	
0.4250	-0.9	-5.7	5.7	36.6	4.7	-0.4	
0.4200	-1.3	3.9	9.1	33.2	10.7	-0.6	
0.4150	-3.3	5.3	7.4	19.1	-6.7	0.4	
0.4100	-3.7	-1.3	4.7	29.1	-7.9	1.2	
0.4050	-3.2	-7.9	-30.4	30.0	0.3	0.9	
0.4000	-1.3	-4.7	2.9	21.9	-1.5	0.4	W
0.3950	-2.2	-11.2	17.8	27.1	-7.0	-0.3	
0.3900	0.9	-16.5	-13.4	33.5	-0.9	-0.1	
0.3850	-2.3	-10.9	23.5	23.5	9.5	2.3	
0.3800	0.4	-4.5	-11.8	-10.2	3.4	-0.1	
0.3750	-0.4	-4.4	1.7	-13.9	-1.6	1.7	

Biuro Usług Kolejowych Sp. z o.o.

Raport danych numerycznych



Data pomiaru: 26.08.2024 14:25:54

Bocznica:

Tor: 102

0.3700	-0.1	-8.8	-2.8	13.9	-7.7	0.8	
0.3650	-2.4	-18.5	10.3	26.6	-6.7	0.7	
0.3600	-1.9	-15.3	-12.8	34.4	6.4	1.0	
0.3550	-2.1	-4.3	-18.3	37.3	19.9	1.8	
0.3500	0.7	4.6	24.3	38.4	-16.7	-1.1	
0.3450	6.2	-9.4	-15.6	66.4	11.2	-0.3	
0.3400	0.1	1.4	12.5	26.5	-6.0	0.4	W
0.3350	1.7	-4.4	-5.0	44.7	-0.8	-0.6	W
0.3300	-0.1	-9.1	-9.6	15.6	-5.4	0.2	
0.3250	1.6	-15.6	19.0	-33.6	-10.2	-0.6	
0.3200	-0.4	-24.0	9.4	-23.3	-8.5	0.7	
0.3150	2.1	-27.3	-16.7	23.0	4.1	3.0	W
0.3100	1.7	-34.1	4.6	17.0	-11.1	-1.1	
0.3050	-1.4	-30.8	-12.4	16.1	15.1	-0.1	
0.3000	5.4	-15.1	10.2	24.1	5.1	-1.6	R
0.2950	4.3	-19.5	-1.4	39.2	-1.1	-1.1	R
0.2900	3.9	-14.8	-7.2	40.9	1.8	-1.9	R
0.2850	0.9	-12.9	7.7	27.7	7.3	2.4	R
#0.2800	5.1	-8.1	7.9	4.6	-2.8	-4.2 #	R
0.2750	7.9	-15.3	-12.4	64.8	-4.8	3.7	R
0.2700	-2.8	-21.1	24.9	15.4	-13.0	-1.0	
0.2650	-0.8	-36.4	-8.5	10.9	-11.3	2.0	
0.2600	-0.5	-36.8	-10.4	15.1	3.3	0.5	
0.2550	-3.6	-38.8	-20.5	25.8	7.1	0.7	
0.2500	-3.7	-15.8	12.3	22.2	21.6	0.1	W
0.2450	-1.8	-8.5	8.4	25.2	-2.7	-0.7	
0.2400	-2.9	-11.6	-1.2	31.0	-2.9	0.5	
0.2350	5.4	-15.4	1.7	38.0	-0.6	0.0	R
0.2300	3.3	-14.5	-0.7	-19.5	4.6	0.3	R
0.2250	14.7	-4.1	-7.5	35.4	8.3	1.1	R
0.2200	9.2	-0.9	6.1	-1.0	-2.0	0.8	R
0.2150	9.4	-7.3	-3.6	-31.4	-2.4	-1.7	R
0.2100	13.0	-4.7			---	---	R